

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/27/2020 Revision date: 05/27/2022 Version: 1.1

# **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture

Trade name : Pinalen Glass & Surface Cleaner

CAS-No. : NA
Product code : 6050591

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Glass and Surface Cleaner

#### 1.3. Supplier

### Manufacturer

AlEn del Norte, S.A. de C.V. Blvd. Gustavo Díaz Ordaz 1000 Los Treviño Santa Catarina, N.L. 66150 - México T 81221000

www.grupoalen.com

### 1.4. Emergency telephone number

Emergency number : 800 424 9300 24 hrs.

# SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Specific target organ H373

toxicity (repeated exposure)

Category 2

Full text of H statements : see section 16

May cause damage to organs through prolonged or repeated exposure

### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H373 - May cause damage to organs through prolonged or repeated exposure Precautionary statements (GHS US) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children. P103 - Read label before use.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P314 - Get medical advice/attention if you feel unwell.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

05/27/2020 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Butyl Glycolether	(CAS-No.) 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373

Full text of hazard classes and H-statements: see section 16

#### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# 5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

# 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

# apparatus. Complete protective clothing.

### **SECTION 6: Accidental release measures**

For non-emergency personnel

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Usar equipo protector, remueva todas las fuentes de ignición, barra el material, use material

absorbente como arena o cualquier otro material absorbente no combustible, recoja el material adsorbido en contenedores adecuados y ciérrelos y mándelos a un confinamiento autorizado. Lave el área con agua, ya que la superficie pudo haber quedado resbalosa.

Protective equipment : Gloves. Protective clothing. Safety glasses.

Emergency procedures : Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

6.1.1.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

05/27/2020 EN (English US) 2/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Incompatible materials : Not corrosive to metals.

### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Butyl Glycolether (111-76-2)		
ACGIH	Local name	2-Butoxyethanol (EGBE)
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

## 8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, aqua liquid . Clear, green liquid.

: Green Green: characteristic

Odor threshold: No data availablepH:  $\approx 8 (7.5 - 8.5)$ Melting point: Not applicableFreezing point: No data availableBoiling point: No data available

05/27/2020 EN (English US) 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available : No data available Relative density : 0.99 - 1.01 g/ml Specific gravity / density Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic No data available Viscosity, dynamic : No data available **Explosion limits** Explosive properties : No data available : No data available Oxidizing properties

### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

## 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

## 10.5. Incompatible materials

Acids. Oxidizing agent.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Butyl Glycolether (111-76-2)		
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)	
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 inhalation rat (ppm)	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))	
ATE US (oral)	1414 mg/kg body weight	
ATE US (gases)	4500 ppmV/4h	
ATE US (vapors)	11 mg/l/4h	
ATE US (dust, mist)	1.5 mg/l/4h	

Skin corrosion/irritation : Not classified  $pH: \approx 8 \ (7.5-8.5)$ 

05/27/2020 EN (English US) 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation	: Not classified
	pH: $\approx 8 (7.5 - 8.5)$
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Butyl Glycolether (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Butyl Glycolether (111-76-2)		
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Irritation.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Butyl Glycolether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

# 12.2. Persistence and degradability

Pinalen Glass & Surface Cleaner (NA)	
Persistence and degradability	Biodegradability: not applicable.
Butyl Glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

Butyl Glycolether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

## 12.4. Mobility in soil

Butyl Glycolether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Ecology - soil	Low potential for adsorption in soil.

# 12.5. Other adverse effects

Other information : No other effects known.

05/27/2020 EN (English US) 5/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 13: Disposal considerations**

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : NA1993 Compounds, cleaning liquid, 3, III

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Compounds, cleaning liquid

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

#### **Transportation of Dangerous Goods**

Not applicable

### Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) : 3 - Flammable liquids

05/27/2020 EN (English US) 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Air transport

Not regulated

# **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

### Butyl Glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

#### **CANADA**

# Butyl Glycolether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

### **EU-Regulations**

No additional information available

### **National regulations**

No additional information available

### 15.3. US State regulations

No additional information available

# **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/27/2022

# Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H373	May cause damage to organs through prolonged or repeated exposure

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

05/27/2020 EN (English US) 7/7